

## Pro-Ject Debut SE II

Manual turntable with fitted cartridge  
Ortofon 510 mk II



### Turntable

- Chassis matt black
- A quiet running AC motor with a two-step metal pulley drives the hub and platter via a flat-ground belt.
- The medium density fibre plinth stands on three height-adjustable rubber-damped aluminium cones.
- The motor is decoupled from the plinth to reduce vibration transmission.
- The platter is a sandwich construction utilising the hub, a fine-balanced aluminium alloy platter weighing 2,2Kg and a felt mat.
- The platter's low-tolerance chrome-plated stainless-steel axle runs on a polished ball bearing in a brass bearing housing.
- Connection to the phono input of the amplifier can be made with connecting cables of your taste through the gold plated phono sockets and earth screw. A standard cable is provided.
- External power supply avoids potential electro-mechanical interference.

### Tonearm Pro-Ject 8.6

- The turntable is supplied with Ortofon 510 mk II MM-cartridge fitted.
- Uniform material: the tonearm tube and bearing housing are constructed from aluminium.
- The headshell and undamped armtube are fashioned from a single piece.
- The inverted horizontal bearings consist of two hardened stainless steel points bearing in sapphire cushions.
- Flexible counterweight shaft avoids vibration at undesirable frequencies.
- Single-screw fixing of armtube allows rotation for easy adjustment of needle azimuth despite fixed headshell.
- The straight armtube with an effective length of 8,6" reduces toe-in error.
- The internal wiring consists of flexible high-purity copper from the headshell right through to the gold-plated phono sockets.

Dimensions W x H x D: With dust cover closed 415 x 118 x 320mm, dust cover open 415 x 365 x 405mm.

Cartridge: Output voltage 3mV. Recommended load resistance 47kohms (MM-input).

The manufacturer reserves the right to alter the technical specifications without notice.