

## Pro-Ject 6 PerspeX SuperPack

Manual turntable with fitted cartridge  
Ortofon MC Valencia and Pro-Ject connection  
cable Connect it Phono RCA-C



### Turntable

- The transparent acrylic plinth stands on three individually height-adjustable Sorbothane®-damped aluminium cones and carries the motor and the sub-chassis. The sub-chassis, made of Corian, rests on three magnetic fields. A supplied spirit level allows easy adjustment of the sub-chassis.
- A quiet running AC motor with a two-step acryl pulley drives the platter's outside edge via a belt.
- The inverted bearing uses a stainless-steel axle carrying a ceramic ball on which the ceramic bearing plate runs.
- The resonance-optimised platter is a sandwich construction utilising a fine-balanced medium density fibre platter weighing 2Kg and a 4mm thick flat-ground layer of vinyl and a screw-down metal record clamp.
- Connection to the phono input of the amplifier can be made with connecting cables of your taste through the gold plated phono sockets and earth screw. A standard cable is provided.
- External power supply avoids potential electro-mechanical interference.

### Tonearm Pro-Ject 9cc Evolution

- The turntable is supplied with Ortofon MC Valencia low output MC-cartridge fitted.
- The headshell and armtube are fashioned from a single piece of carbon-fibre.
- Conical armtube avoids standing wave reflections.
- Inverted tonearm bearing comprises four hardened stainless tips in ABEC7 spec ballraces.
- Rings provide very solid arm bearing housings. The massive outside ring is open to avoid resonances.
- Sorbothane®-damped counterweight effectively counteracts unwanted resonances.
- The counterweights supplied are suitable for cartridges weighing between 5 - 7,5g, 7 - 10g, 9 - 11g or 10 - 14g.
- Counterweight shaft lowered to record level reduces cantilever forces and dynamic wow when playing warped records.
- Solid armbase permits accurate height adjustment of armtube and VTA (vertical tracing angle).
- Single-screw fixing of armtube allows rotation for easy adjustment of needle azimuth despite fixed headshell.
- The straight armtube with an effective length of 9" reduces toe-in error.
- Silicone-damped armlift can be adjusted to suit working height of the arm.
- The internal wiring consists of flexible high-purity copper from the headshell right through to the gold-plated phono sockets.

Dimensions W x H x D: With dust cover closed 460 x 160 x 365mm, dust cover open 460 x 420 x 465mm.  
Cartridge: Output voltage 0,45mV. Recommended load resistance 100 ohms (MC-input).

The manufacturer reserves the right to alter the technical specifications without notice.