

Pro-Ject Record Box USB

MM Phono Pre-amplifier with
A/D converter and USB output



Good sound from sound technology

- Metal case shields the electronics from vibrational and electromagnetic interference
- Optimal channel separation through dual-mono circuitry
- Special low-noise ICs used
- Gold plated RCA connection sockets
- Outboard power supply included

Features

- Digitalisation of analogue signals for recording direct to disk via USB with suitable recording programs
- Small size allows installation close to record player
- Automatic recognition, without additional driver, by standard PC
- Runs on Windows XP®, Windows Vista®, Windows 7® and Mac OS operating systems

Technical specifications

Input impedance:	47kohms/100pF
Gain:	32dB
Output voltage typically:	200mV/1kHz at 5mV
Noise floor:	82dB (88dB / A weighted)
THD:	<0,05%
RIAA-equalisation curve accuracy:	20Hz - 20kHz / max. 0,5dB
A/D converter:	Burr Brown PCM2904 16-Bit Delta Sigma
Sampling rates:	32, 44,1 and 48kHz
USB-output:	digital serial data protocol USB 1.1
Outboard power supply:	16V/200mA AC, suitable for your country's mains supply
Power consumption:	16V/100mA AC
Dimensions W x H x D (D with sockets):	109 x 33 x 75 (88)mm
Weight:	350g without power supply

The manufacturer reserves the right to alter the technical specifications without notice.