

Pro-Ject RPM 5 SuperPack

Manual turntable with electronic speed change and fitted cartridge Pro-Ject Pick it MC1H



Turntable

- Chassis piano-lacquered dark grey
- A quiet running AC motor with a two-step metal pulley drives the hub and platter via a flat-ground belt.
- The medium density fibre plinth stands on three height-adjustable rubber-damped aluminium cones.
- The motor is decoupled from the plinth to reduce vibration transmission.
- The resonance-optimised platter is a sandwich construction utilising the hub, an medium density fibre platter, a cork mat (a standard felt mat is also supplied) and a screw-down record clamp.
- The platter's low-tolerance chrome-plated stainless-steel axle runs on a Teflon bearing plate in a sintered bronze bearing housing.
- Central metal block optimises centre of gravity and damps main bearing.
- Electronic speed change for 33/45 r.p.m.. Switching to 78 r.p.m. is done manually.
- Connection to the phono input of the amplifier can be made with connecting cables of your taste through the gold plated phono sockets and earth screw. A standard cable is provided.
- External power supply avoids potential electro-mechanical interference.

Tonearm Pro-Ject 9c

- The turntable is supplied with Pro-Ject Pick it MC1H high output MC-cartridge fitted.
- Conical carbon-fibre armtube avoids standing wave reflections.
- Low mass aluminium headshell securely glued to armtube.
- The inverted bearings consist of four hardened stainless steel points bearing in sapphire cushes.
- Rings provide very solid arm bearing housings. The outside ring is open to avoid resonances.
- Design of counterweight effectively counteracts unwanted resonances.
- Counterweight shaft lowered to record level reduces cantilever forces and dynamic wow when playing warped records.
- Solid armbase permits accurate height adjustment of armtube and VTA (vertical tracing angle).
- Single-screw fixing of armtube allows rotation for easy adjustment of needle azimuth despite fixed headshell.
- The straight armtube with an effective length of 9" reduces toe-in error.
- Silicone-damped armlift can be adjusted to suit working height of the arm.
- The internal wiring consists of flexible high-purity copper from the headshell right through to the gold-plated phono sockets.

Dimensions W x H x D: 371 x 145 x 300mm. Dust cover Cover it optional. W x H x D: 525 x 290 x 425mm.
Cartridge: Output voltage 2,2mV. Recommended load resistance 47kohms (MM-input).

The manufacturer reserves the right to alter the technical specifications without notice.
The colours in the picture may differ slightly from the actual article due to inaccuracies in the printing process.