

Pro-Ject RPM 6.1 SB SuperPack

Manual turntable with electronic speed change, and fitted cartridge
Ortofon MC Samba



Turntable

- A quiet running AC motor with a two-step metal pulley drives the acrylic hub and platter via a flat-ground belt.
- The medium density fibre plinth stands on three height-adjustable Sorbothane®-damped aluminium cones.
- The motor is decoupled from the plinth to reduce vibration transmission.
- The resonance-optimised platter is a sandwich construction utilising the hub, an medium density fibre platter, a 4mm thick flat-ground layer of vinyl and a brass record puck.
- The inverted bearing uses a stainless-steel axle carrying a ceramic ball on which the ceramic bearing plate runs.
- Electronic speed change for 33/45 r.p.m.. Switching to 78 r.p.m. is done manually.
- Central metal block optimises centre of gravity and damps main bearing.
- Connection to the phono input of the amplifier can be made with connecting cables of your taste through the gold plated phono sockets and earth screw. A standard cable is provided.
- External power supply avoids potential electro-mechanical interference.

Tonearm Pro-Ject 9c

- The turntable is supplied with Ortofon MC Samba low output MC-cartridge fitted.
- Conical carbon-fibre armtube avoids standing wave reflections.
- Low mass aluminium headshell securely glued to armtube.
- The inverted bearings consist of four hardened stainless steel points bearing in sapphire cushions.
- Rings provide very solid arm bearing housings. The outside ring is open to avoid resonances.
- Design of counterweight effectively counteracts unwanted resonances.
- Counterweight shaft lowered to record level reduces cantilever forces and dynamic wow when playing warped records.
- Solid armbase permits accurate height adjustment of armtube and VTA (vertical tracing angle).
- Single-screw fixing of armtube allows rotation for easy adjustment of needle azimuth despite fixed headshell.
- The straight armtube with an effective length of 9" reduces toe-in error.
- Silicone-damped armlift can be adjusted to suit working height of the arm.
- The internal wiring consists of flexible high-purity copper from the headshell right through to the gold-plated phono sockets.

Dimensions W x H x D: 385 x 170 x 330mm. Dust cover Cover it optional. W x H x D: 525 x 290 x 425mm.
Cartridge: Output voltage 0,30mV. Recommended load resistance > 10 ohms (MC-input).

The manufacturer reserves the right to alter the technical specifications without notice.