

Pro-Ject RPM 9.1 SuperPack 1 & 2

Manual turntable with fitted cartridge
Ortofon MC Rondo Red or Sumiko Blue Point No. 2
and Pro-Ject Speed Box SE



Turntable

- Chassis and motor housing piano-lacquered dark grey
- A quiet running AC motor with a two-step acryl pulley drives the platter's outside edge via a belt.
- The medium density fibre plinth stands on three height-adjustable Sorbothane®-damped aluminium cones. A supplied spirit level allows easy adjustment. Granulate filled plinth guarantees constant damping.
- The motor is mounted in a separate metal housing to eliminate vibration transmission.
- The resonance-optimised platter is a sandwich construction utilising an acrylic platter weighing 3,5Kg and a brass record puck.
- The inverted bearing uses a stainless-steel axle carrying a ceramic ball on which the ceramic bearing plate runs.
- Central metal block optimises centre of gravity and damps main bearing.
- Connection to the phono input of the amplifier can be made with connecting cables of your taste through the gold plated phono sockets and earth screw. A standard cable is provided.
- External power supply avoids potential electro-mechanical interference.

Tonearm Pro-Ject 9cc

- **SuperPack 1:** The turntable is supplied with Ortofon MC Rondo Red low output MC-cartridge fitted.
- **SuperPack 2:** The turntable is supplied with Sumiko Blue Point No. 2 high output MC-cartridge fitted.
- The headshell and armtube are fashioned from a single piece of carbon-fibre.
- Conical armtube avoids standing wave reflections.
- Inverted tonearm bearing comprises four hardened stainless tips in ABEC7 spec ballraces.
- Rings provide very solid arm bearing housings. The outside ring is open to avoid resonances.
- Design of counterweight effectively counteracts unwanted resonances.
- Counterweight shaft lowered to record level reduces cantilever forces and dynamic wow when playing warped records.
- Solid armbase permits accurate height adjustment of armtube and VTA (vertical tracing angle).
- Single-screw fixing of armtube allows rotation for easy adjustment of needle azimuth despite fixed headshell.
- The straight armtube with an effective length of 9" reduces toe-in error.
- Silicone-damped armlift can be adjusted to suit working height of the arm.
- The internal wiring consists of flexible high-purity copper from the headshell right through to the gold-plated phono sockets.

Dimensions W x H x D: Including motor unit 440 x 180 x 325mm.

Dust cover Cover it optional. W x H x D: 525 x 290 x 425mm.

SuperPack 1, cartridge: Output voltage 0,30mV. Recommended load resistance > 10 ohms (MC-input).

SuperPack 2, cartridge: Output voltage 2,5mV. Recommended load resistance 47kohms (MM-input).

The manufacturer reserves the right to alter the technical specifications without notice.
The colours in the picture may differ slightly from the actual article due to inaccuracies in the printing process.