

Pro-Ject Tube Box II

Tube MM/MC Phono Pre-amplifier



Good sound from sound technology

- Metal case shields the electronics from vibrational and electromagnetic interference
- Dual-Mono circuitry utilising two double triodes for improved channel separation
- Subsonic filter selection switch located at the rear of the unit
- Gold plated RCA connection sockets
- Outboard power supply included

Features

- Amplification and RIAA equalisation for MM and MC cartridges
- Phono MM/MC selection switch located at the rear of the unit

Technical specifications

Tubes:	2 x ECC83 (12AX 7A)
Input impedance, MM:	47kohms/120pF
Input impedances, MC:	100ohms/120pF
Gain, MM:	40dB
Output voltage typically:	300mV/1kHz at 3mV (MM input)
Gain, MC:	60dB
Output voltage typically:	300mV/1kHz at 0,3mV (MC input)
Noise floor, MM:	84dB (94dB / A weighted)
Noise floor, MC:	67dB (75dB / A weighted)
THD, MM:	0,05%
THD, MC:	0,08%
RIAA-equalisation curve accuracy:	20Hz - 20kHz / max. 0,5dB
Subsonic filter:	at 18Hz with 18dB/octave
Outboard power supply:	16V/1.000mA AC, suitable for your country's mains supply
Power consumption:	16V/410mA AC
Dimension W x H x D:	103 x 76 x 141mm
Weight:	810g without power supply

The manufacturer reserves the right to alter the technical specifications without notice.



Available in silver or black finish